I	/ISIBL	F	FI	VI	155	10	N	NO	TA	TI	\cap	N	5

Inspector:	1			
Date of Inspection:	5/1/11			
Shift: 1st Shift or (2nd Sl	nift T	ime: C0500		
Unit	Visual Inspection <u>NORMAL</u> or <u>ABN</u> ORMAL		Comments	
Visible Emission From Shaker	Nor	Processor		
Visible Emission From Discharge Conveyor System	Non			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS				
Inspector: Masintaris				
Date of Inspection:				
Shift: (1 st Shift) or 2 nd Shift	Time:	6130		
Unit Visu	27 L		Comments	
NORN or ABNOF	<u>//AL</u>			:
Visible Emission From Shaker \(\sum_{\mathcal{O}}'	12			
Visible Emission From Discharge Conveyor System				

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS			
Inspector: Rick PALO	mo			
Date of Inspection: 5/2/	(
Shift: 1 st Shift or 2 nd Sh	nift / Ti nd	me: 5:00 AM		
Unit	Visual Inspection <u>NORMAL</u> or ABNORMAL		Comments	
Visible Emission From Shaker	NOR	, restate physical and restate the fill of		
Visible Emission From Discharge Conveyor System	20 R			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- **Opacity** is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

D.1.12 Daily Visible Emissions Notations Per Each Daylight Shift

(Stack SDS 04)

AI2IRFF I	EMISSIO	I ON N	AHONS	
Inspector:	0	/		

Date of Inspection:

Time:

Smit. 1 Smit or 2 Si	HIL EHI	5°pm				
Control of the contro	Visual Inspection <u>NORMAL</u> or <u>ABN</u> ORMAL		Ç	omments	· · · · · · · · · · · · · · · · · · ·	
Visible Emission From Shaker	NOR					
Visible Emission From Discharge Conveyor System	NOR					

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS				
Inspector: Rick PAL	QMC				
Date of Inspection: $5/2$	/11				
Shift: 1 st Shift or 2 nd Sh	E .	me: 5800			
Unit	Visual		Comments		
	Inspection NORMAL or				
	<u>ABN</u> ORMAL		 	 	
Visible Emission From Shaker	NOR	(communications and constitution)			
Visible Emission From Discharge Conveyor System	NOR				

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

D.1.12 Daily Visible Emissions Notations Per Each Daylight Shift

(Stack SDS 04)

Inspector: R Long			
Date of Inspection: 5/3///			
Shift: 1 st Shift or 2 nd Shift	Time: 5 pm		
Unit Visual Inspection	1	Comments	

•	Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be	e expected to

cause the greatest emissions.
Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS

Visible Emission From Shaker

Visible Emission From Discharge Conveyor System NORMAL

ABNORMAL

NOR

NOR

D.1.12 Daily Visible Emissions Notations Per Each Daylight

(Stack SDS 04)

A 12 IDEE EIMIS	SOION	NOI	AHUNS	
Inspector:	ck	PAI	OMO	

Date of Inspection:

Shift: I shift or 2 sr	int ii	me: 5800.AM		
The second secon	Visual Inspection <u>NORMAL</u> or ABN ORMAL		Comments	
Visible Emission From Shaker	NOR			
Visible Emission From Discharge Conveyor System	NOR	, port and the second second		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS						
Inspector: R LONG							
Date of Inspection: 5/4	/11						
Shift: (st Shift or 2nd Shi	ift Ti	me:	5 pm				
Unit	Visual Inspection				Comments		
Agency and the control of the contro	<u>NORMAL</u> or <u>ABN</u> ORMAL						
Visible Emission From Shaker	Non						
Visible Emission From Discharge Conveyor System	Nac						

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

D.1.12 Daily Visible Emissions Notations Per Each Daylight Shift

(Stack SDS 04)

A 1910FF FINISSIOI	VIVOTATIONS	
Inspector: Rick	PALOMO	

Date of Inspection: 5/5/11

VICIBLE EMISSION NOTATIONS

Shift: 1st Shift or 2nd Shift | Time: 5', 00 AM

2	ind	5:00 AM		
Unit	Visual		Comments	
	Inspection NORMAL			
	or ABNORMAL			
Visible Emission From Shaker	NOK	**************************************		
Visible Emission From				
Discharge Conveyor System	NOR	, and the second		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS	
Inspector: Rick PALOMO	
Date of Inspection: 5/6/11	
Shift: 1st Shift or 2nd Shift 2nd	Time: 5° 00 AM

	end	6. CO A.		
Emit	Visual Inspection <u>NORMAL</u> or		Comments	
Visible Emission From Shaker	NOR	**************************************		·
Visible Emission From Discharge Conveyor System	NOR	, married and section of the section		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS					
Inspector: R Lora						
Date of Inspection: 5/6/	11					
Shift: 1 st Shift or 2 nd Sh	ift Time	e: 5 pm				
Umit	Visual		e e e e e e e e e e e e e e e e e e e	Comments		
	Inspection NORMAL					
The first from the first t	or <u>ABN</u> ORMAL			1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
Visible Emission From Shaker	NOL					
Visible Emission From						
Discharge Conveyor System	Non					

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS ,			
Inspector:	emptos			
Date of Inspection:	111			
Shift: 1 st Shift or 2 nd Sh	nift Ti	ime: 500AM		
Unit	Visual		Comments	
	Inspection NORMAL			
The state of the s	or <u>ABN</u> ORMAL			·
Visible Emission From Shaker	Nov	Australia di		
Visible Emission From				
Discharge Conveyor System	Nar	**Company of the Company of the Comp		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- **Opacity** is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS	<u></u>	
Inspector: Alexandro Hernandez		
Date of Inspection: 5 - 7-11		
Shift: 1st Shift of 2 nd Shift Time:		
Unit Visual Inspection NORMAL	Comments	
or <u>ABN</u> ORMAL		
Visible Emission From Shaker NOP		
Visible Emission From Discharge Conveyor System		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS

TICIDEL LIMOCICIT ITO ITT			~-	
Inspector:	n 91			
Date of Inspection:	5/8/11			
Shift: 1 st Shift or 2 nd Shift	T)	ime: @ 0 S60		
Unit	Visual		Comments	
	Inspection <u>NORMAL</u> or <u>ABN</u> ORMAL			
Visible Emission From Shaker	Nor	. Carpet Manual		
Visible Emission From Discharge Conveyor System	Non			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			
Inspector: Alexandro H	ernan dez			
Date of Inspection: 5-	8-11			
Shift: 1 st Shift or 2 nd Shi	ift T	ime: 5pM		
The same of the sa	3.7.	JUM	2: 1	
	Visual		Comments	
	Inspection			
Fig. 1. Sept. 1. Sept	NORMAL			
	or			
	<u>ABN</u> ORMAL			
Visible Emission From Shaker				
	Nov	Confession of the Confession o		
Visible Emission From				
Discharge Conveyor System				
Districting Conveyor System	NOR		 	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	AHONS				
Inspector:	ompton				
Date of Inspection: 5/9/	/1/ "				
Shift: 1 st Shift or (2 nd)Sh	nift 2nd T	ime: 5-00AM			
La	Visual		Comn	nents	
	Inspection				
	NORMAL				
	or ABNORMAL	-		- -	
Visible Emission From Shaker	Nor				
Visible Emission From					
Discharge Conveyor System	Nax	Angus considerate and anti-real anti-real anti-real and anti-real anti-r			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

Revised 2/10/09

VISIBLE EMISSION NOTATIONS Inspector: Alono Date of Inspection: Shift: 1st Shift or 2nd Shift, Time: 5,00 AM Unit Visual Comments Inspection NORMAL **ABN**ORMAL Visible Emission From Shaker NOR Visible Emission From

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

Revised 2/10/09

Discharge Conveyor System

NOR

VISIBLE EMISSION NOTA	ATIONS				
Inspector: R LONG					
Date of Inspection: 5//6	111				
Shift: 1st Shift or 2nd Sh	nift Ti	me: 5 pm			
Unit	Visual	/	Comments		
	Inspection NORMAL		• •	,	
And the second of the second o	or ABNORMAL				
Visible Emission From Shaker	NOR				
Visible Emission From Discharge Conveyor System	Nex				

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			
Inspector: R LONS				
Date of Inspection: 5/11	111			
Shift: (Shift or 2 nd Sh	lift Ti	me: 5 pM		
Unit	Visual Inspection <u>NOR</u> MAL		Comments	
The second secon	or <u>ABN</u> ORMAL		· · · · · · · · · · · · · · · · · · ·	
Visible Emission From Shaker	NOR			
Visible Emission From Discharge Conveyor System	Nor			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

AISIBLE FINISSION NOTA	AHONS			
Inspector: Pick PA	COMO			
Date of Inspection: 5/12	///			
Shift: 1 st Shift or 2 nd Sh	nift T	ime: 5300AM		
Unit Visible Emission From Shaker	Visual Inspection <u>NORMAL</u> or <u>ABN</u> ORMAL		Comments	
VISIBLE EINISSION FROM Shaker	NOK	^{N-18} ptonembeggggggggggggggggggggggggggggggggggg		
Visible Emission From Discharge Conveyor System	NOR	, пинциариндинициналлиндинуу		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	NTIONS			
Inspector: R Lows				
Date of Inspection: 5//2	111			
Shift: Shift or 2hd St	nift T	ime: 5pm		
Unit	Visual		Comments	
	Inspection NORMAL			
	or ABNORMAL			
Visible Emission From Shaker	NUR			
Visible Emission From Discharge Conveyor System	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS	· · · · · · · · · · · · · · · · · · ·		
Inspector: Rick k	ALONO			
Date of Inspection: 5/12	2/11			
Shift: 1 st Shift or 2 nd Sf	nift Ti	me: SIOCAM		
L Unit	Visual		Comments	
	Inspection			
The state of the s	<u>NOR</u> MAL			
Compared to the Property Compared to the Com	or		***	
Control of Control Control of Con	<u>ABN</u> ORMAL			
Visible Emission From Shaker	alad			
	1001	No contraction of the contractio		
Visible Emission From				
Discharge Conveyor System	MARIA			
	10000	No communication and address of the control of the		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			
Inspector: S. Guerza	DQ			
Date of Inspection:				
Shift: 1 st Shift or 2 nd Sh	ift Second Ti	me: Sam		
Unit	Visual		Comments	
The second of th	Inspection NORMAL			
	or ABNORMAL	· · · · · · · · · · · · · · · · · · ·	* . **	
Visible Emission From Shaker	NOR	DOWN FOR	2 MAINTENANCE	
Visible Emission From Discharge Conveyor System	NOR	DOWN FOR	MAINTENANTE	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			
Inspector: R Lo	Wa			
Date of Inspection:	1111			
Shift: (Shift or 2nd Sh	ift' Ti	me: Spm		
Unit	Visual Inspection NORMAL or		Comments	
Visible Emission From Shaker	ABNORMAL			
	HOR			
Visible Emission From Discharge Conveyor System	HOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	AHONS			
Inspector:	Dogen			
Date of Inspection:	5/15/11			
Shift: 1 st Shift or 2 nd Sh	nift T	ime:0 0500		
Unit	Visual Inspection NORMAL or ABNORMAL		Comments	
Visible Emission From Shaker	Nor	editillor.	ATRI DOWN	
Visible Emission From Discharge Conveyor System	Nor	onlane	V	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	IIONS			
Inspector: R LONG				
Date of Inspection: 5/15	111			
Shift: (1 st Shift or 2 nd Sh	ift Ti	me: SpM		
L	Visual		Comments	
	Inspection			
	NORMAL			
Control of the Contro	or ABNORMAL			
Visible Emission From Shaker	. would			
	NUC			
Visible Emission From	110.0			
Discharge Conveyor System	NUR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	MONS				
Inspector, RICK PALC	MG				
Date of Inspection: 5/17	//11				
Shift: 1 st Shift or 2 nd Sh	nift Ti	me: 5800 Am			
Unit	Visual			Comments	,
	Inspection NORMAL				
	or ABNORMAL		2.		
Visible Emission From Shaker	NOR	чинаризарины какарамуна катина батар			
Visible Emission From Discharge Conveyor System	NOR	, production of the control of the c			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

Revised 2/10/09

VISIBLE EMISSION NOTA	ATIONS			
Inspector: R lar	5			
Date of Inspection: 5//7	711			
Shift: (st Shift or 2nd Sh	nift Ti	me: Spm		
Unit	Visual Inspection NORMAL or ABNORMAL		Comments	
Visible Emission From Shaker	NOR			
Visible Emission From Discharge Conveyor System	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS			
Inspector: Rick PALO	MO			
Date of Inspection: 5/18/	11			
Shift: 1 st Shift or 2 nd Sh	nift Ti 2nd	me: 5860		
Unit	Visual Inspection <u>NORMAL</u> or		Comments	
Visible Emission From Shaker	ABNORMAL NOR	- Again Sellona my sold and beauty policy and		
Visible Emission From Discharge Conveyor System	NOR	vuud evilitäija kaleen kaiten viilin ka		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS			
Inspector: R Lox	19			
Date of Inspection: 5//	8/11			
Shift: Shift or 2nd Sr	nift Ti	me: 5 pm		
	Visual Inspection <u>NORMAL</u> or ABNORMAL		Comments	
Visible Emission From Shaker	NOR			
Visible Emission From Discharge Conveyor System	Nor			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS			
Inspector: RICK PALOMO			
Date of Inspection: 5/19/11			
Shift: 1 st Shift or 2 nd Shift	Time: 5% 00AM		
Unit Visual Inspectio NORMA or ABNORM	on L	Comments	
Visible Emission From Shaker	-unbounding operate medical processors and collection of memority		
Visible Emission From Discharge Conveyor System Nor	manufacture and home company and an analysis of the company an		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS				
Inspector: RICK PA	HLOMO				
Date of Inspection: 5/20	/11				
Shift: 1 st Shift or 2 nd Sh	oifit T	ime: 5:00AM	* And the Management of the Control		
e unit	Visual Inspection			Comments	
	<u>NORMAL</u> or <u>ABN</u> ORMAL				
Visible Emission From Shaker	NOR	· C_ellintationssellementelesespelesestellesepp			
Visible Emission From Discharge Conveyor System	NOR	Lucia suprano sultanta Naparita		·	

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS			
Inspector: R LON	'વ			
Date of Inspection:	20/1/			
Shift: 18 Shift or 270 Sh	nift Tim	e: 5 pm		
Unit	Visual Inspection NORMAL or		Comments	
Visible Emission From Shaker	NORMAL		·	
Visible Emission From Discharge Conveyor System	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS				
Inspector: RICK PAL	OMO				
Date of Inspection: 5/21	/11				
Shift: 1 st Shift or 2 nd Sh	oift T	ime: 5800 AM			
Unit	Visual			Comments	,
	Inspection		4		
	NORMAL				
	or ABNORMAL		· 	 2	
Visible Emission From Shaker	NOR	se ^{contraction} of an attention determinant and attention to the second attention of the second attention and attention at the second attention attention at the second attent			
Visible Emission From					
Discharge Conveyor System	NOR	_{and the second}			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background:

VISIBLE EMISSION NOTA	ATIONS				
Inspector: Alexandro	Hermodez				
Date of Inspection:	-1/1)				
Shift: 1 st Shift or 2 ^{ng} St	rift/ T	ime:			
SUmite	Visual Inspection NORMAL or ABNORMAL		C	omments	
Visible Emission From Shaker	NOR				
Visible Emission From Discharge Conveyor System	NOR				

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS				
Inspector: RICK PA	OMO				
Date of Inspection: 5/22	111				
Shift: 1 st Shift •r 2 nd Sh	niftj Ti	me: 500 AM			
E de la companya de	Visual		Comments		
	Inspection				
The state of the s	NORMAL				
	or		 		
Control of	ABNORMAL		 ·		
Visible Emission From Shaker	NOK	Considere expressions			
Visible Emission From	1				
Discharge Conveyor System	NOR				

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOT	ATIONS				
Inspector: RICK PA	Long				
Date of Inspection: 5/23	3/11				
Shift: 1 st Shift or 2 nd Sh	nift T	ime: 5,100AM			
Unit	Visual			Comments	,
	Inspection		7		
	NORMAL		<i>t</i> ,		
Control of the contro	or ABNORMAL			 	
Visible Emission From Shaker	NOR	, market and the second and the seco			
Visible Emission From					
Discharge Conveyor System	NOR	Annexistation of management of the Contraction of the Contraction			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS				
Inspector: RICK PA	-Lomo				
Date of Inspection: 5/24	/11				
Shift: 1 st Shift or 2 nd Sh) nd	me: 5°00Am			
- Unit	Visual			Comments	
	Inspection				
	NORMAL		s je		
And the second s	or ABNORMAL	. "			
Visible Emission From Shaker	NOR	, the All-Andread and Annual Andread Annual Andread Annual Andread Annual Andread Annual Annu			
Visible Emission From					
Discharge Conveyor System	NOR	No communication of the property of the state of the stat			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			
Inspector:				
Date of Inspection: 5/2	5/			
Shift: 1 st Shift or 2 nd Sh	ift Ti 2nd	me: 5100 AM		
Unit	Visual		Comments	
	Inspection			
And the second of the second o	NORMAL			
	or		**	
The state of the s	ABNORMAL			
Visible Emission From Shaker	NOR	· Autoritation and an annual contraction of the con		
Visible Emission From				
Discharge Conveyor System	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

Timo:		
17:00		
	Comments	
	**	

_		
	Time: 17:00	Comments

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

D.1.12 Daily Visible Emissions Notations Per Each Daylight Snn.

(Stack SDS 04)

VISIBLE EMISSION NOTA	ATIONS			
Inspector: RICK &	ALOMO			
Date of Inspection:	5/26/11			
Shift: 1 st Shift or 2 nd Si	nift T	ime: 5:00 AM		
Unit	Visual		Comments	
	Inspection			
	NORMAL or			
The property of the control of the c	ABNORMAL		•	
Visible Emission From Shaker	NOR	* The state of the		
Visible Emission From				
Discharge Conveyor System	NOR	 - G-And-de-grand-field and Contraction of contraction and Contrac		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	.HONS				
Inspector:					
Stormer					
Inspector: Stormer Pate of Inspection:	-ll.				
Shift: (1 st Shift) or 2 nd Sh	ift T	ime:			
		17:00			
	Visual			Comments	•
	Inspection		*		
	NORMAL		Z.,		
	Or			ii e	
Control of the Contro	ABNORMAL				
Visible Emission From Shaker	2/20				
	NOQ	Section 1997			
Visible Emission From					
Discharge Conveyor System	Non				
		1			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS				
Inspector: RICK P	HOMO				
Date of Inspection: 5/27	7/11				
Shift: 1 st Shift or ¹ 2 nd Sh	nift T 2nd	ime: 500AM			
Unit	Visual			Comments	
	Inspection NORMAL		•		
And the state of t	or ABNORMAL				
Visible Emission From Shaker	NOR	The state of the s			
Visible Emission From		AND RECOGNISE OF THE PROPERTY AND			
Discharge Conveyor System	NOR				

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS			
Inspector:	toma			
Date of Inspection:	1 7 1			
	5/27/11			
Shift: (1 st Shift) or 2 nd Sh	nift Ti	me: 17:00		
- Drift	Visual Inspection NORMAL		Comments	
	or ABNORMAL	***************************************	 7	
Visible Emission From Shaker	Non			
Visible Emission From Discharge Conveyor System	Nol	and the second s		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EIVISSION NOTA	AHONS			
Inspector: RICK PAL	OMO			
Date of Inspection: 5/	28/11			
Shift: 1 st Shift or 2 nd Sh	ift T	ime: 6:00AM		
l discussion de Unit	Visual		Comments	
	Inspection NORMAL			
	or <u>ABN</u> ORMAL	. "		
Visible Emission From Shaker	NOR	ngga and an		
Visible Emission From Bischarge Conveyor System	NOR	and the second		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS			
Inspector:			
Storney			
Date of Inspection:			
5128111			
Shift: (1st Shift) or 2nd Shift	ime:		
	11:00		
Unit Visual		Comments	,
Inspection			
NORMAL			
Stationary Charles and the state of the stat		**************************************	
<u>ABN</u> ORMAL			
Visible Emission From Shaker			
Nac	- SERVICE-		
Visible Emission From			
Discharge Conveyor System			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

Revised 2/10/09

VISIBLE EMISSIÓN NOTA	ATIONS			
Inspector: PICK PA	LOMO			
Date of Inspection: 5/2	29/11			
Shift: 1 st Shift or 2 nd Sh	nift Ti 2n d	me: 5.'00 AM		
Unit	Visual		Comments	
	Inspection			
	<u>NORMAL</u>			•
A Company of the Comp	or ABNORMAL			
Visible Emission From Shaker	NOR			
Visible Emission From				
Discharge Conveyor System	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			
Inspector: RICK PAL	OMO			
Date of Inspection: 5/30	2/11			
Shift: 1 st Shift or 2 nd Sh 20		me: 5300		
- Unit	Visual	-	Comments	
	Inspection			
	NORMAL			
The state of the s	ABNORMAL		**************************************	
Visible Emission From Shaker	NOR			
Visible Emission From Discharge Conveyor System	NOR	- Caracagoriman destructivamente destruc		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTAT	rions							
Inspector: RICK PALOMO								
Date of Inspection: 5/31	/11			:				
Shift: 1 st Shift or 2 nd Shif		Time:	5800A1	Ч				
Unit	Visual Inspection NORMAL or ABNORMAL			-		Comments		
Visible Emission From Shaker	NOL	-100			•			
Visible Emission From Discharge Conveyor System	NOR							

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.